

## **FAKTABLAD P300**

		COOLPIX P300		
Effective pixels		12.2 megapixels		
Image sensor		1/2.3-in. type RGB CMOS		
Lens		Optical 4.2x zoom, NIKKOR lens		
	Focal length	4.3-17.9m	m (35mm [135] format equivalent to 24-100 mm)	
	Aperture	f/1.8-4.9		
	Lens construction	7 elements	s in 6 groups ( no ED glass element, one HRI lens )	
Digital zoom		Maximum 2x (35mm [135] format equivalent to approx. 200 mm)		
Focus range (from lens)		Approx. 30 cm (1 ft.) to infinity (at wide-angle setting), approx. 60 cm (2 ft.) to infinity (at telephoto setting), Macro mode: approx. 3 cm (1.2 in.) to infinity (at wide-angle setting), approx. 30 cm (1 ft.) to infinity (at telephoto setting)		
Vibration Reduction (VR)		Lens-shift type for stills and movies		
	Other blur-reduction functions	Motion De	tection*1, BSS (Best Shot Selector)	
ISO sensitivity (Standard output sensitivity)		ISO 160, 200, 400, 800, 1600, 3200 (4000 x 3000), Auto (ISO 160 to 1600), Fixed range auto (ISO 160 to 400, 160 to 800)		
LCD monitor		7.5 cm (3-in.), approx. 921k-dot, wide-viewing angle TFT LCD monitor (VGA) with Clear Color Display, anti-reflection coating and brightness adjustment		
Storage media		Internal memory (approx. 90 MB), SD/SDHC/SDXC memory card*2 (exFAT compatible, UHS not compatible)		
Smart Portrait System	Face-priority AF/max. number of faces to be detected	12	Face priority, Face-priority AE, Face Zoom-in	
	Skin Softening	•	During shooting/playback	
	Smile Timer	•	Up to three smiling faces can be detected, can be switched ON/OFF	
	Blink Proof	_	_	
	Blink Warning	•	Can be switched ON/OFF	
	In-Camera Red-Eye Fix	•	Automatically corrects red eye digitally	
Subject Tracking*3		•	Auto lock-on: not available/AF activation: available/Tracking Restart: available	



## **FAKTABLAD P300**

		COOLPIX P300	
Scene modes		18 scene modes*1 (Portrait, Landscape, Sports, Night portrait, Party/indoor, Beach, Snow, Sunset, Dusk/dawn, Close-up, Food, Museum, Fireworks show, Black and white copy, Panorama, Pet portrait, Backlighting*2, Night Landscape)	
	Scene Auto Selector	6 scene modes + Auto mode (Portrait, Landscape, Night portrait, Night landscape, Close-up, Backlighting)	
Sport Continuous mode		_	
Movie		HD 1080p: 1920 x 1080 (30 fps), HD 720p: 1280 x 720 (30 fps), VGA: 640 x 480 (30 fps)	
	HS movie	● (15/60/120 fps, no sound)	
D-Lighting		•	
Active D-Lighting		_	
Color Options		— (Creative Slider is adopted)	
Quick Retouch		•	
Slide show		[No music or image effect]	
File-sorting functions		_	
Battery charging with USB		With supplied charging AC Adapter: approx. 4 h charging time When camera is connected with powered on PC*3 via supplied USB cable: approx. # h charging time	
Interface/Direct print compatibility		Hi-Speed USB/PictBridge	
Supported languages		26 languages (products for Japan feature Japanese/English only)	
Projector		_	
Power sources		Rechargeable Li-ion Battery EN-EL12 (1050 mAh), AC Adapter EH-62F (option)	
Number of shots per charge (battery life)*5		Approx. 240 frames with EN-EL12	
Dimensions (W x H x D)		Approx. 103.0 x 58.3 x 32.0 mm/ (excluding projections)	
Weight*6		Approx. 189 g/ (including battery and SD memory card)	

<sup>\*1</sup> Can be set with Mode dial. (Excluding Special effects and Scene Auto Selector) \*2 HDR effect level can be selected from the menu (Off, Level 1-3) \*3 Depends on power supply from PC \*4 Based on CIPA Standards for measuring life of batteries \*5 Based on CIPA Guidelines, DCG-005-2009

## Kontaktinformation

För pressbilder, vänligen besök <a href="http://press.nikon.se">http://press.nikon.se</a> För övrig information, se <u>www.nikon.se</u> eller vänligen kontakta Irena Strozyk, Marknadsansvarig på Nikon telefon 08-594 109 04, 0709-95 58 25 eller e-post strozyk@nikon.se