

FAKTABLAD L23

			COOLPIX L23	
Effective pixels		10.1 megapixels		
Image sensor		1/2.9-in. type RGB CCD		
Lens		Optical 5x zoom, NIKKOR lens		
	Focal length	4.0-20.0mm (35mm [135] format equivalent to 28-140 mm)		
	Aperture	f/2.7-6.8		
	Lens construction	6 elements in 5 groups (one ED glass element)		
Digital zoom		Maximum 4x (35mm [135] format equivalent to approx. 560 mm)		
Focus range (from lens)		Approx. 30 cm (1 ft.) to infinity (at wide-angle setting), approx. 60 cm (2 ft.) to infinity (at telephoto setting), Macro mode: approx. 3 cm (1.2 in.) to infinity (at wide-angle setting)		
Vibration Reduction (VR)		Electronic type for still images		
	Other blur-reduction functions	Motion Dete	ection, BSS (Best Shot Selector)	
ISO sensitivity (Standard output sensitivity)		Auto (ISO 80 to 1600) [T.B.A.]		
LCD monitor		6.7 cm (2.7-in.), approx. 230k-dot, TFT LCD monitor (QVGA) with brightness adjustment		
Storage media		Internal memory (approx. 22 MB [T.B.A.]), SD/SDHC/SDXC memory card*1		
Smart Portrait System	Face-priority AF/max. number of faces to be detected	12	Face priority, Face-priority AE, Face Zoom-in	
	Skin Softening	•	During shooting/playback	
	Smile Timer	•	Smart Portrait mode ^{*2} , Up to three smiling faces can be detected, can not be switched ON/OFF	
	Blink Proof	•	Takes two sequential shots, can be switched ON/OFF	
	Blink Warning	•	Can be switched ON/OFF	
	In-Camera Red-Eye Fix	•	Automatically corrects red eye digitally, pre-flashes	
Subject Tracking*3		<u> </u>	_	

^{*1} Not compatible with Multi Media Card (MMC)
*2 Function equivalent to Smile Timer
*3 Tracks a designated subject automatically



FAKTABLAD L23

		COOLPIX L23	
Scene modes		17 scene modes (Portrait, Landscape, Night portrait, Party/indoor, Beach, Snow, Sunset, Dusk/dawn, Night landscape, Close-up, Food, Museum, Fireworks show, Black and white copy, Backlighting, Panorama assist, Sports)	
	Scene Auto Selector	6 scene modes + Auto mode (Portrait, Landscape, Night portrait, Night landscape, Close-up, Backlighting)	
Sport Continuous mode			
Movie		VGA: 640 x 480 (30 fps), QVGA: 320 x 240 (30 fps)	
	HS movie	_	
D-Lighting D-Lighting			
Active D-Lighting			
Color Options			
Quick Retouch			
Slide show		[No music or image effect]	
File-sorting functions		List by date mode	
Battery charging with USB		-	
Interface/Direct print compatibility		Hi-Speed USB/PictBridge	
Supported languages		26 languages (products for Japan feature Japanese/English only)	
Projector			
Power sources		R6/AA-size battery x 2 (alkaline/lithium: optional), Rechargeable Ni-MH Batteries EN-MH2-B2 (2 batteries: optional)/Rechargeable Ni-MH Batteries EN-MH2-B4 (4 batteries: optional), AC Adapt EH-65A (optional)	
Number of shots per charge (battery life)*1		Approx. 250 frames (with alkaline batteries)	
Dimensions (W x H x D)		Approx. 96.7 x 59.9 x 29.3 mm/3.8 x 2.4 x 1.2 in. (excluding projections)	
Weight*2		Approx. 170 g/6.0 in. (including battery and SD memory card)	

Kontaktinformation

För pressbilder, vänligen besök http://press.nikon.se För övrig information, se www.nikon.se eller vänligen kontakta Irena Strozyk, Marknadsansvarig på Nikon telefon 08-594 109 04, 0709-95 58 25 eller e-post strozyk@nikon.se