

## **FAKTABLAD S6100**

			COOLPIX S6100	
Effective pixels		16.0 megapixels		
Image sensor		1/2.3-in. type RGB CCD		
Lens		Optical 7x zoom, NIKKOR lens		
	Focal length	5.0-35.0mm (35mm [135] format equivalent to 28-196 mm)		
	Aperture	f/3.7-5.6		
	Lens construction	9 elements i	n 7 groups (one ED glass element)	
Digital zoom		Maximum 4x (35mm [135] format equivalent to approx. 784 mm)		
Focus range (from lens)		Approx. 50 cm (1 ft. 8 in.) to infinity (at wide-angle setting), approx. 1.1 m (3 ft. 7 in.) to infinity (at telephoto setting), Macro mode: approx. 3 cm (1.2 in.) to infinity (1 or 2 positions from the widest end)		
Vibration Reduction (VR)		Lens-shift type		
	Other blur-reduction functions	Motion Dete	ction, BSS (Best Shot Selector)	
ISO sensitivity (Standard output sensitivity)		ISO 80, 100, 200, 400, 800, 1600, 3200 (4608 x 3456), Auto (ISO 80 to 1600) Fixed range auto (ISO 80 to 400, 80 to 800)		
LCD monitor		7.5 cm (3-in.), approx. 460k-dot, wide-viewing angle TFT LCD monitor (HVGA), [Resistive touch panel], Clear color display, anti-reflection coating and brightness adjustment		
Storage media		Internal memory (approx. 20 MB), SD/SDHC/SDXC memory card*1		
Smart Portrait System	Face-priority AF/max. number of faces to be detected	12	Face priority, Face-priority AE, Face Zoom-in	
	Skin Softening	•	During shooting/playback	
	Smile Timer	•	Up to three smiling faces can be detected, can be switched ON/OFF	
	Blink Proof	•	Takes two sequential shots, can be switched ON/OFF	
	Blink Warning	•	Can be switched ON/OFF	
	In-Camera Red-Eye Fix	•	Automatically corrects red eye digitally, pre-flashes	
Subject Tracking*2*3		•	Auto lock-on: not available/AF activation: available/Tracking Restart: not available	

<sup>\*1</sup> Not compatible with MultiMediaCard (MMC) 
\*2 Tracks a designated subject automatically 
\*3 Can be set with Mode dial



## **FAKTABLAD S6100**

		COOLPIX S6100	
Scene modes		18 scene modes*1 (Portrait, Landscape, Sports, Night Portrait, Party/indoor, Beach, Snow, Sunset, Dusk/dawn, Night landscape, Close-up, Pet portrait, Food, Museum, Fireworks show, Black and white copy, Paint, Backlighting, Panorama assist)	
	Scene Auto Selector	6 scene modes + Auto mode (Portrait, Landscape, Night portrait, Night landscape, Close-up, Backlighting)	
Sport Continuous mode		-	
Movie		HD 720p: 1280 x 720 (30 fps), VGA: 640 x 480 (30 fps), QVGA: 320 x 240 (30 fps)	
	HS movie	_	
D-Lighting		•	
Active D-Lighting		-	
Color Options		•	
Quick Retouch			
Slide show		Built-in; Background music: 3 kinds, Effect: 3 kinds	
File-sorting functions		Auto Sort mode, Favorite Pictures playback, List by date mode	
Battery charging with USB		With supplied charging AC Adapter: approx. 3 h 20min charging time When camera is connected with powered on PC*2 via supplied USB cable: approx. 3 h 50min charging time	
Interface/Direct print compatibility		Hi-Speed USB/PictBridge	
Supported languages		26 languages	
Projector		_	
Power sources		Rechargeable Li-ion Battery EN-EL12 (1050 mAh) AC Adapter EH-62F (option)	
Number of shots per charge (battery life)*3		Approx. 210 frames with EN-EL12	
Dimensions (W x H x D)		Approx. 97.9 x 58.0 x 26.6 mm/3.9 x 2.3 x 1.1 in. (excluding projections)	
Weight*4		Approx. 175 g/6.2 oz. (including battery and SD memory card)	

<sup>\*1</sup> Excludes Scene Auto Selector and draw mode \*2 Depends on power supply from PC 
\*3 Based on CIPA Standards for measuring life of batteries \*4 Based on CIPA Guidelines, DCG-005-2009

## Kontaktinformation

För pressbilder, vänligen besök <a href="http://press.nikon.se">http://press.nikon.se</a> För övrig information, se <a href="www.nikon.se">www.nikon.se</a> eller vänligen kontakta Irena Strozyk, Marknadsansvarig på Nikon telefon 08-594 109 04, 0709-95 58 25 eller e-post <a href="mailto:strozyk@nikon.se">strozyk@nikon.se</a>